

### New Jersey Department of Health and Senior Services

# HAZARDOUS SUBSTANCE FACT SHEET

Common Name: SODIUM DICHROMATE

CAS Number: 10588-01-9 DOT Number: UN 1479

#### HAZARD SUMMARY

- \* Sodium Dichromate can affect you when breathed in.
- \* **Sodium Dichromate** is a CARCINOGEN--HANDLE WITH EXTREME CAUTION.
- \* Contact can severely irritate and burn the skin and eyes with possible eye damage. Prolonged skin contact can cause blisters and deep ulcers.
- \* Breathing Sodium Dichromate can irritate the nose, throat and lungs causing coughing, wheezing and/or shortness of breath.
- \* Breathing **Sodium Dichromate** can cause a sore and/or a hole in the "bone" dividing the inner nose (septum), sometimes with bleeding, discharge or crusting.
- \* Sodium Dichromate may cause a skin allergy. If allergy develops, very low future exposure can cause itching and a skin rash.
- \* Sodium Dichromate may cause an asthma-like allergy. Future exposure can cause asthma attacks with shortness of breath, wheezing, cough, and/or chest tightness.
- \* **Sodium Dichromate** may damage the kidneys.

#### **IDENTIFICATION**

**Sodium Dichromate** is a red or red-orange, odorless, crystalline (sand-like) substance. It is used as a wood preservative, in electroplating, and to make other *Chromium* compounds.

#### **REASON FOR CITATION**

- \* Sodium Dichromate is on the Hazardous Substance List because it is regulated by OSHA and cited by ACGIH, DOT, NIOSH, NTP, IARC, HHAG and EPA.
- \* This chemical is on the Special Health Hazard Substance List because it is a **CARCINOGEN**.
- \* Definitions are provided on page 5.

# HOW TO DETERMINE IF YOU ARE BEING EXPOSED

The New Jersey Right to Know Act requires most employers to label chemicals in the workplace and requires public employers to provide their employees with information and training concerning chemical hazards and controls. The federal OSHA Hazard Communication Standard, 1910.1200, requires private employers to provide similar training and information to their employees.

RTK Substance number: 1695

Date: September 1986 Revision: April 2000

\_\_\_\_\_\_

- \* Exposure to hazardous substances should be routinely evaluated. This may include collecting personal and area air samples. You can obtain copies of sampling results from your employer. You have a legal right to this information under OSHA 1910.1020.
- \* If you think you are experiencing any work-related health problems, see a doctor trained to recognize occupational diseases. Take this Fact Sheet with you.

#### WORKPLACE EXPOSURE LIMITS

The following exposure limits are for *Chromates* (measured as *Chromium*):

OSHA: The legal airborne permissible exposure limit

(PEL) is **0.1 mg/m<sup>3</sup>**, not to be exceeded at any

time.

NIOSH: The recommended airborne exposure limit is

**0.001 mg/m<sup>3</sup>** averaged over a 10-hour workshift.

ACGIH: The recommended airborne exposure limit is

**0.05 mg/m<sup>3</sup>** averaged over an 8-hour workshift.

\* **Sodium Dichromate** is a CARCINOGEN in humans. There may be <u>no</u> safe level of exposure to a carcinogen, so all contact should be reduced to the lowest possible level.

#### WAYS OF REDUCING EXPOSURE

- \* Enclose operations and use local exhaust ventilation at the site of chemical release. If local exhaust ventilation or enclosure is not used, respirators should be worn.
- \* A regulated, marked area should be established where **Sodium Dichromate** is handled, used, or stored.
- \* Wear protective work clothing.
- \* Wash thoroughly <u>immediately</u> after exposure to **Sodium Dichromate** and at the end of the workshift.
- \* Post hazard and warning information in the work area. In addition, as part of an ongoing education and training effort, communicate all information on the health and safety hazards of **Sodium Dichromate** to potentially exposed workers.

This Fact Sheet is a summary source of information of <u>all potential</u> and most severe health hazards that may result from exposure. Duration of exposure, concentration of the substance and other factors will affect your susceptibility to any of the potential effects described below.

\_\_\_\_\_

#### **HEALTH HAZARD INFORMATION**

#### **Acute Health Effects**

The following acute (short-term) health effects may occur immediately or shortly after exposure to **Sodium Dichromate**:

- \* Contact can severely irritate and burn the skin and eyes with possible eye damage.
- \* Breathing Sodium Dichromate can irritate the nose, throat and lungs causing coughing, wheezing and/or shortness of breath.

#### **Chronic Health Effects**

The following chronic (long-term) health effects can occur at some time after exposure to **Sodium Dichromate** and can last for months or years:

#### Cancer Hazard

- \* **Sodium Dichromate** is a CARCINOGEN in humans. It has been shown to cause lung and throat cancer.
- \* Many scientists believe there is no safe level of exposure to a carcinogen.

#### **Reproductive Hazard**

\* There is no evidence that **Sodium Dichromate** affects reproduction. This is based on test results presently available to the New Jersey Department of Health and Senior Services from published studies.

#### **Other Long-Term Effects**

- \* Prolonged skin contact can cause blisters and deep ulcers.
- \* Breathing **Sodium Dichromate** can cause a sore and/or a hole in the "bone" dividing the inner nose (septum), sometimes with bleeding, discharge or crusting.
- \* Sodium Dichromate may cause a skin allergy. If allergy develops, very low future exposure can cause itching and a skin rash.
- \* **Sodium Dichromate** may cause an asthma-like allergy. Future exposure can cause asthma attacks with shortness of breath, wheezing, cough, and/or chest tightness.
- \* Sodium Dichromate may damage the kidneys.

#### **MEDICAL**

#### **Medical Testing**

Before beginning employment and at regular times after that, the following are recommended:

- \* Kidney function tests.
- \* If you suspect nose or lung effects, seek prompt medical attention.

\* Also check your skin daily for little bumps or blisters, the first sign of "Chrome ulcers." If not treated early, these can last for years after exposure.

If symptoms develop or overexposure is suspected, the following are recommended:

- \* Evaluation by a qualified allergist, including careful exposure history and special testing, may help diagnose skin allergy.
- \* Lung function tests. These may be normal if the person is not having an attack at the time of the test.

Any evaluation should include a careful history of past and present symptoms with an exam. Medical tests that look for damage already done are <u>not</u> a substitute for controlling exposure.

Request copies of your medical testing. You have a legal right to this information under OSHA 1910.1020.

#### Mixed Exposures

\* Because smoking can cause heart disease, as well as lung cancer, emphysema, and other respiratory problems, it may worsen respiratory conditions caused by chemical exposure. Even if you have smoked for a long time, stopping now will reduce your risk of developing health problems.

#### **Conditions Made Worse By Exposure**

\* Persons allergic to *Chromium* compounds may be more likely to develop a skin allergy to **Sodium Dichromate**.

#### WORKPLACE CONTROLS AND PRACTICES

Unless a less toxic chemical can be substituted for a hazardous substance, **ENGINEERING CONTROLS** are the most effective way of reducing exposure. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release. Isolating operations can also reduce exposure. Using respirators or protective equipment is less effective than the controls mentioned above, but is sometimes necessary.

In evaluating the controls present in your workplace, consider: (1) how hazardous the substance is, (2) how much of the substance is released into the workplace and (3) whether harmful skin or eye contact could occur. Special controls should be in place for highly toxic chemicals or when significant skin, eye, or breathing exposures are possible.

In addition, the following controls are recommended:

- \* Where possible, automatically transfer **Sodium Dichromate** from drums or other storage containers to process containers.
- \* A Class I, Type B, biological safety hood should be used when mixing, handling, or preparing **Sodium Dichromate**.

Good **WORK PRACTICES** can help to reduce hazardous exposures. The following work practices are recommended:

- \* Workers whose clothing has been contaminated by **Sodium Dichromate** should change into clean clothing promptly.
- \* Do not take contaminated work clothes home. Family members could be exposed.
- \* Contaminated work clothes should be laundered by individuals who have been informed of the hazards of exposure to **Sodium Dichromate**.
- \* Eye wash fountains should be provided in the immediate work area for emergency use.
- \* If there is the possibility of skin exposure, emergency shower facilities should be provided.
- \* On skin contact with Sodium Dichromate, immediately wash or shower to remove the chemical. At the end of the workshift, wash any areas of the body that may have contacted Sodium Dichromate, whether or not known skin contact has occurred.
- \* Do not eat, smoke, or drink where **Sodium Dichromate** is handled, processed, or stored, since the chemical can be swallowed. Wash hands carefully before eating, drinking, smoking, or using the toilet.
- \* Use a vacuum or a wet method to reduce dust during cleanup. DO NOT DRY SWEEP.
- \* When vacuuming, a high efficiency particulate air (HEPA) filter should be used, <u>not</u> a standard shop vacuum.

#### PERSONAL PROTECTIVE EQUIPMENT

WORKPLACE CONTROLS ARE BETTER THAN PERSONAL PROTECTIVE EQUIPMENT. However, for some jobs (such as outside work, confined space entry, jobs done only once in a while, or jobs done while workplace controls are being installed), personal protective equipment may be appropriate.

OSHA 1910.132 requires employers to determine the appropriate personal protective equipment for each hazard and to train employees on how and when to use protective equipment.

The following recommendations are only guidelines and may not apply to every situation.

#### **Clothing**

- \* Avoid skin contact with **Sodium Dichromate**. Wear protective gloves and clothing. Safety equipment suppliers/manufacturers can provide recommendations on the most protective glove/clothing material for your operation.
- \* All protective clothing (suits, gloves, footwear, headgear) should be clean, available each day, and put on before work.

#### **Eye Protection**

\* Eye protection is included in the recommended respiratory protection.

## Respiratory Protection

#### IMPROPER USE OF RESPIRATORS IS DANGEROUS.

Such equipment should only be used if the employer has a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing and medical exams, as described in OSHA 1910.134.

- \* Where the potential exists for exposure over **0.001** mg/m<sup>3</sup> (as *hexavalent Chromium*), use a MSHA/NIOSH approved supplied-air respirator with a full facepiece operated in a pressure-demand or other positive-pressure mode. For increased protection use in combination with an auxiliary self-contained breathing apparatus operated in a pressure-demand or other positive-pressure mode.
- \* Exposure to 15 mg/m³ (as hexavalent Chromium) is immediately dangerous to life and health. If the possibility of exposure above 15 mg/m³ (as hexavalent Chromium) exists, use a MSHA/NIOSH approved self-contained breathing apparatus with a full facepiece operated in a pressure-demand or other positive-pressure mode.

#### HANDLING AND STORAGE

- \* Prior to working with **Sodium Dichromate** you should be trained on its proper handling and storage.
- \* A regulated, marked area should be established where **Sodium Dichromate** is handled, used, or stored.
- Sodium Dichromate must be stored to avoid contact with COMBUSTIBLES; ORGANIC MATERIALS (such as PAPER, WOOD and FUELS); STRONG ACIDS (such as HYDROCHLORIC, **SULFURIC** and NITRIC); ALCOHOLS; HYDRAZINE; ACETIC ANHYDRIDE; TRINITROTOLUENE; CARBIDES; AMINES; SLAKED **OXIDIZING AGENTS** LIME; (such PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE); MERCURY CYANIDES; and SILICON since violent reactions occur.
- \* Store in tightly closed containers in a cool, dry, well-ventilated area away from HEAT and METALS.
- \* Wherever **Sodium Dichromate** is used, handled, manufactured, or stored, use explosion-proof electrical equipment and fittings.

#### **QUESTIONS AND ANSWERS**

- Q: If I have acute health effects, will I later get chronic health effects?
- A: Not always. Most chronic (long-term) effects result from repeated exposures to a chemical.

- Q: Can I get long-term effects without ever having short-term effects?
- A: Yes, because long-term effects can occur from repeated exposures to a chemical at levels not high enough to make you immediately sick.
- Q: What are my chances of getting sick when I have been exposed to chemicals?
- A: The likelihood of becoming sick from chemicals is increased as the amount of exposure increases. This is determined by the length of time and the amount of material to which someone is exposed.
- Q: When are higher exposures more likely?
- A: Conditions which increase risk of exposure include <u>dust releasing operations</u> (grinding, mixing, blasting, dumping, etc.), <u>other physical and mechanical processes</u> (heating, pouring, spraying, spills and evaporation from large surface areas such as open containers), and <u>"confined space" exposures</u> (working inside vats, reactors, boilers, small rooms, etc.).
- Q: Is the risk of getting sick higher for workers than for community residents?
- A: Yes. Exposures in the community, except possibly in cases of fires or spills, are usually much lower than those found in the workplace. However, people in the community may be exposed to contaminated water as well as to chemicals in the air over long periods. This may be a problem for children or people who are already ill.
- Q: Don't all chemicals cause cancer?
- A: No. Most chemicals tested by scientists are not cancercausing.
- Q: Should I be concerned if a chemical causes cancer in animals?
- A: Yes. Most scientists agree that a chemical that causes cancer in animals should be treated as a suspected human carcinogen unless proven otherwise.
- Q: But don't they test animals using much higher levels of a chemical than people usually are exposed to?
- A: Yes. That's so effects can be seen more clearly using fewer animals. But high doses alone don't cause cancer unless it's a cancer agent. In fact, a chemical that causes cancer in animals at high doses could cause cancer in humans exposed to low doses.

The following information is available from:

New Jersey Department of Health and Senior Services Occupational Health Service PO Box 360 Trenton, NJ 08625-0360 (609) 984-1863 (609) 292-5677 (fax)

Web address: http://www.state.nj.us/health/eoh/odisweb/

#### **Industrial Hygiene Information**

Industrial hygienists are available to answer your questions regarding the control of chemical exposures using exhaust ventilation, special work practices, good housekeeping, good hygiene practices, and personal protective equipment including respirators. In addition, they can help to interpret the results of industrial hygiene survey data.

#### **Medical Evaluation**

If you think you are becoming sick because of exposure to chemicals at your workplace, you may call personnel at the Department of Health and Senior Services, Occupational Health Service, who can help you find the information you need.

#### **Public Presentations**

Presentations and educational programs on occupational health or the Right to Know Act can be organized for labor unions, trade associations and other groups.

#### Right to Know Information Resources

The Right to Know Infoline (609) 984-2202 can answer questions about the identity and potential health effects of chemicals, list of educational materials in occupational health, references used to prepare the Fact Sheets, preparation of the Right to Know survey, education and training programs, labeling requirements, and general information regarding the Right to Know Act. Violations of the law should be reported to (609) 984-2202.

\_\_\_\_\_

#### **DEFINITIONS**

**ACGIH** is the American Conference of Governmental Industrial Hygienists. It recommends upper limits (called TLVs) for exposure to workplace chemicals.

A carcinogen is a substance that causes cancer.

The **CAS number** is assigned by the Chemical Abstracts Service to identify a specific chemical.

A combustible substance is a solid, liquid or gas that will burn.

A **corrosive** substance is a gas, liquid or solid that causes irreversible damage to human tissue or containers.

**DEP** is the New Jersey Department of Environmental Protection.

**DOT** is the Department of Transportation, the federal agency that regulates the transportation of chemicals.

**EPA** is the Environmental Protection Agency, the federal agency responsible for regulating environmental hazards.

A fetus is an unborn human or animal.

A **flammable** substance is a solid, liquid, vapor or gas that will ignite easily and burn rapidly.

The **flash point** is the temperature at which a liquid or solid gives off vapor that can form a flammable mixture with air.

HHAG is the Human Health Assessment Group of the federal FP $\Delta$ 

**IARC** is the International Agency for Research on Cancer, a scientific group that classifies chemicals according to their cancer-causing potential.

A **miscible** substance is a liquid or gas that will evenly dissolve in another.

mg/m<sup>3</sup> means milligrams of a chemical in a cubic meter of air. It is a measure of concentration (weight/volume).

**MSHA** is the Mine Safety and Health Administration, the federal agency that regulates mining. It also evaluates and approves respirators.

A **mutagen** is a substance that causes mutations. A **mutation** is a change in the genetic material in a body cell. Mutations can lead to birth defects, miscarriages, or cancer.

**NAERG** is the North American Emergency Response Guidebook. It was jointly developed by Transport Canada, the United States Department of Transportation and the Secretariat of Communications and Transportation of Mexico. It is a guide for first responders to quickly identify the specific or generic hazards of material involved in a transportation incident, and to protect themselves and the general public during the initial response phase of the incident.

**NCI** is the National Cancer Institute, a federal agency that determines the cancer-causing potential of chemicals.

**NFPA** is the National Fire Protection Association. It classifies substances according to their fire and explosion hazard.

**NIOSH** is the National Institute for Occupational Safety and Health. It tests equipment, evaluates and approves respirators, conducts studies of workplace hazards, and proposes standards to OSHA.

**NTP** is the National Toxicology Program which tests chemicals and reviews evidence for cancer.

**OSHA** is the Occupational Safety and Health Administration, which adopts and enforces health and safety standards.

**PEOSHA** is the Public Employees Occupational Safety and Health Act, a state law which sets PELs for New Jersey public employees.

**ppm** means parts of a substance per million parts of air. It is a measure of concentration by volume in air.

A **reactive** substance is a solid, liquid or gas that releases energy under certain conditions.

A **teratogen** is a substance that causes birth defects by damaging the fetus.

**TLV** is the Threshold Limit Value, the workplace exposure limit recommended by ACGIH.

The **vapor pressure** is a measure of how readily a liquid or a solid mixes with air at its surface. A higher vapor pressure indicates a higher concentration of the substance in air and therefore increases the likelihood of breathing it in.

Common Name: **SODIUM DICHROMATE** 

DOT Number: UN 1479
NAERG Code: 140
CAS Number: 10588-01-9

Hazard rating	NJDHSS	NFPA
FLAMMABILITY	0	-

1

REACTIVITY
CARCINOGEN

POISONOUS GASES ARE PRODUCED IN FIRE CONTAINERS MAY EXPLODE IN FIRE

Hazard Rating Key: 0=minimal; 1=slight; 2=moderate; 3=serious; 4=severe

#### FIRE HAZARDS

- \* Use water to extinguish fire.
- \* POISONOUS GASES ARE PRODUCED IN FIRE.
- \* CONTAINERS MAY EXPLODE IN FIRE.
- \* Use water spray to keep fire-exposed containers cool.
- Sodium Dichromate may ignite combustibles (wood, paper and oil).
- \* If employees are expected to fight fires, they must be trained and equipped as stated in OSHA 1910.156.

#### SPILLS AND EMERGENCIES

If **Sodium Dichromate** is spilled, take the following steps:

- \* Evacuate persons not wearing protective equipment from area of spill until clean-up is complete.
- \* Cover with sand and place in covered containers for disposal.
- \* Ventilate and wash area after clean-up is complete.
- \* It may be necessary to contain and dispose of **Sodium Dichromate** as a HAZARDOUS WASTE. Contact your Department of Environmental Protection (DEP) or your regional office of the federal Environmental Protection Agency (EPA) for specific recommendations.
- \* If employees are required to clean-up spills, they must be properly trained and equipped. OSHA 1910.120(q) may be applicable.

FOR LARGE SPILLS AND FIRES immediately call your fire department. You can request emergency information from the following:

CHEMTREC: (800) 424-9300 NJDEP HOTLINE: (609) 292-7172

#### **HANDLING AND STORAGE** (See page 3)

#### **FIRST AID**

In NJ, for POISON INFORMATION call 1-800-764-7661

#### **Eye Contact**

\* Immediately flush with large amounts of water. Continue without stopping for at least 30 minutes, occasionally lifting upper and lower lids. Seek medical attention immediately.

#### **Skin Contact**

\* Quickly remove contaminated clothing. Immediately wash contaminated skin with large amounts of water.

#### **Breathing**

- \* Remove the person from exposure.
- \* Begin rescue breathing (using universal precautions) if breathing has stopped and CPR if heart action has stopped.
- \* Transfer promptly to a medical facility.

#### PHYSICAL DATA

Water Solubility: Highly soluble

#### OTHER COMMONLY USED NAMES

#### **Chemical Name:**

Chromic Acid, Disodium Salt

#### Other Names:

Chromium Sodium Oxide; Disodium Dichromate; Bichromate of Soda

Not intended to be copied and sold for commercial

not intended to be copied and sold for commercial purposes.

NEW JERSEY DEPARTMENT OF HEALTH AND SENIOR SERVICES

#### **Right to Know Program**

PO Box 368, Trenton, NJ 08625-0368 (609) 984-2202

-----